



WELDING ENGINEERS (NZ) LTD

PH : 09 634 1949 email : sales@wenzl.co.nz

CutSkill Cutting Nozzles

CutSkill provides a range of type 41 & type 44 cutting nozzles for use with oxygen - acetylene and oxygen - LP Gas or Natural gas respectively. These two seat designed nozzles are for use with CutSkill, COMET 3, Multi-purpose and Sabre cutting torches.

The type 41 nozzles are manufactured from copper that provides effective heat resistance and the type 44 are of two-piece construction incorporating a copper shroud.



CutSkill Type 41 Cutting Nozzles (Oxy/Acetylene)

<i>Part No</i>	<i>Size</i>	<i>Cutting Thickness mm</i>	<i>Fuel gas flow L/min @ 100kPa</i>	<i>Total Oxygen Flow & pressure L/min @ kPa</i>
206046	6	1-6	2.0	11 (200)
206047	8	6-10	3.5	20 (200)
206048	12	12-20	4.0	38 (200)
206049	15	25-75	7.0	75 (350)
206050	20	100-125	9.0	134 (400)

CutSkill Type 44 Cutting Nozzles (Oxy/LP Gas or Natural gas)

<i>Part No</i>	<i>Size</i>	<i>Cutting Thickness mm</i>	<i>Fuel gas flow L/min @ 100kPa</i>	<i>Total Oxygen Flow & pressure L/min @ kPa</i>
206025	6	3-6	2.0	17(200)
206026	8	6-12	3.5	30 (200)
206028	12	12-20	4.5	58 (250)
206029	15	25-75	5.5	99 (400)
206030	20	100-125	6.5	171 (400)