



MULTI PROCESS WELDING INVERTER

00

3 IN **1** Multi process

190A POWER

CIGWELD

BLUEVENDM X7190

OPTI START

92







SYNERGIC 3-IN-1 WELDING INVERTER WITH MIG PLATE THICKNESS SELECTION

AUTO SET MIG PROCESS

2

h



SPOOL GUN COMPATIBLE

CIGWELD

2-ROLL DRIVE

SMALLER, LIGHTER, YET MORE POWER

The BlueVENOM XF190 is loaded with Xtra Functions that pack a serious sting to get the job done!

30% smaller than some other machines in its class and lighter in weight at only 9.5kg's - BlueVENOM is here - ready to release your inner WelditudeTM!

Boasting a built for comfort MIG gun, this Synergic 3-in-1 predator takes the guesswork out of welding with its pre-defined QuickSet plate thickness selection settings – simply select your gas (if you're using it), wire diameter and your plate thickness – then arc away!

Navigate with ease through the bright blue 4.3" LED panel with a single control knob and glove-friendly easy-press buttons.

Not only can you now 'Plug n' Weld' using a 10 Amp (230V/240V) plug, you can also customise the way your arc starts through 'Opti'Start' technology – delivering refined arc characteristics in the most popular processes of MIG (QuickSet and Manual, Gas & Gasless). Additionally in MMAW/STICK Electrode mode we have added a Voltage Reduction Device (VRD) for maximum safety and DC-Lift TIG is provided with Trigger Button On/Off or Dial Amperage Control functions when using optional TIG Torches.

CAN YOU HARNESS THE POWER?

CIGWELD

BLUEVENOM

0

Ο

A USER FRIENDLY INTERFACE WITH EASY PRESS BUTTONS DESIGNED WHEN WEARING WELDING GLOVES.

0

CHOOSE GAS TYPE

ARGON for Aluminium & SilBronze MIX Gas for Welding Steels & Stainless GASLESS for using Gasless MIG Wires.

TRIGGER MODE Selection

2T for standard On/Off MIG/TIG mode. 4T for locking on the trigger for long runs <u>- cruis</u>e control for welding!

SELECT YOUR Welding Process

MIG/TIG/MMA (Stick)

ADVANCED & Background Settings

Toggle through features and background settings including; Inductance, Burnback, OptiStart (independent Soft and Hard Starts) in MIG Modes plus Hard Start and Arc Force in STICK Mode.

EURO GUN Connectivity

Equipped with a EURO Connection allowing for multiple MIG gun options. ERGONOMIC & ROBUST Carry Handle

0

0

DIGITAL DISPLAY

The BLUEVENOM XF190 is equipped with a 4.3" bright blue Sharp LED display which provides optimal clarity both indoors and outdoors.

WIRE DIAMETER Selection

Choose Wire sizes; 0.6mm, 0.8mm, 0.9mm, 1.0mm and MAN (Manual) MIG Mode for welding - wire size selection not applicable in MAN Mode

WIRE INCH & Gas Purge

Easy access Wire Inch and Gas Purge functions at the tip of your fingers.

1-PRESS CONTROL KNOB

User friendly, simple screen navigation.

POLARITY CHANGE LEAD

Change depending on process used.

BLUEVENOM XF190

EASY TO USE, EASY TO SET

- QuickSet, simple to set & weld
- Spool Gun compatible, great for Aluminium (sold separately)
- Suitable for 100mm and 200mm Diameter Spools
- MIG Gasless and MIG Gas Shielded
- Bright Blue LED Digital Meter for outdoor use
- Fine tuning of Pre-Set Wire Speed & Volts
- Full control over manual settings
- Welding wire size selection
- Recommended MIG & TIG welding thickness range 0.6mm 10mm
- Recommended STICK welding thickness range 1.6mm 12mm
- Factory Settings reset feature
- You can weld most metals including Mild Steel, Stainless Steel, Aluminium and Bronze
- CIGWELD have specially configured this machine to be able to produce great welding results from 230V/240V x 10A power



WIRE DRIVE SYSTEM

2x Roll All-Driven Wire Drive system for smoother and effortless feedability.

AWESOME OUTPUT FOR A SMALL MACHINE

The BlueVENOM XF190 delivers a maximum output of 190 Amps DC in MIG and TIG Modes, which means the machine is capable of welding metals from 0.6mm up to 10mm. In STICK mode the machine is capable of welding metals from 1.6mm up to 12mm in thickness.

XTRA FUNCTIONS

The BlueVENOM XF190 is the perfect solution for light fabrication, maintenance and repairs or for DIY around the home, workshop, worksite, or farm without compromising on quality, safety and performance! With the avid welder in mind, CIGWELD have introduced "**Opti-Start**", a feature that allows the user to customise their starting arc characteristics through Soft and Hard Start controls. To top it off, the unit has the following built-in features:

- 2 x Roll All-Driven (top & bottom) Wire Drive system
- MIG Adjustable Wire Burnback
- MIG Soft & Hard Start
- MIG Wire Inch button
- MIG Gas Purge button
- MIG Side door wire installation, side loader
- MIG Anti de-spooling safety feature
- Spool Gun Compatible
- STICK with Voltage Reduction Device (VRD) built-in for Safe Welding
- STICK Hot Start
- STICK Arc Force
- STICK Anti-Stick
- Thermal Overload Protection
- TIG Foot Control Compatible
- TIG Dial Remote Torch Compatible

TECHNICAL SPECIFICATIONS

Power Supply (Voltage):	Single-Phase 230V/240V +/-15%
Australian Standard:	AS 60974.1:2020
Frequency Hertz:	50/60Hz
Supply Lead and Plug supplied:	10 Amp Plug
Generator Rating:	10 kVA (at 0.8 Power Factor) at Max Amps
Amperage Range (MIG):	30 - 190A
Voltage Range:	15.5 - 26.0V
MIG (GMAW) Duty Cycle @ 40°C, 10 minutes:	185 Amps @ 9%
	72 Amps @ 60%
	56 Amps @ 100%

	160 Amps @ 10%
STICK (MMAW) Duty Cycle @ 40°C, 10 minutes:	65 Amps @ 60%
	50 Amps @ 100%
TIG (GTAW) Duty Cycle @ 40°C, 10 minutes:	190 Amps @ 10%
	77 Amps @ 60%
	60 Amps @ 100%
Nominal DC Open Circuit Voltage in MIG Mode:	52V
Open Circuit Voltage (VRD On) STICK Mode:	<35V
Weight of Power Source:	9.5Kg
Power Source Dimensions (mm):	L: 465 x W: 190 x H: 340
Weight of Full Package:	16.6Kg
Full Package Dimensions (mm):	L: 530 x W: 295 x H: 345
Protection Class:	IP 21S

MULTIPROCESS CONNECTIVITY



MIG GUN: For welding Mild Steel, Stainless Steel, Aluminium and Bronze.



SPOOL GUN: (Sold Separately): For greater precision welding of Aluminium, Stainless Steel and Bronze.



ELECTRODE HOLDER: For welding Mild Steel, Stainless Steel, Cast Iron and dissimilar metals.



TIG TORCH (LIFT-TIG & DIAL REMOTE): (Sold Separately) For welding any commercial metal (excluding aluminium alloys).

9

3



FOOT CONTROL: (Sold Separately) For remote adjustment of welding current on TIG mode.




WARRANTY PERIOD

2-Year conditional warranty. See terms and conditions at cigweld.com.au or in the **Operating Manual, included** with the machine.





MIG (GMAW / FCAW): 190A 0.6-1.0mm: Solid MIG wires & 0.8-0.9mm gasless MIG wires



Power source is suitable for 2.0mm,

2.5mm, 3.2mm and 4.0mm electrode sizes.

STICK (MMAW): 160A





This unit features a Lift TIG function that provides smooth starting and running characteristics across a broad range of applications.



LIFT TIG

Plate Thickness Control (QuickSet) Reduce setup time. Welding parameters are automatically set based on wire diameter, material type and plate thickness.





Spool Gun Compatible

Up to 10mm Plate Thickness

Power source is suitable to weld



ф

INCH



Compatible with SGT-250 Spool Gun in Manual Mode.

Easy Access Gas Purge Button Easy access Gas Purge button on front display enables user to purge shielding gas through MIG Gun.

Easy Access Wire Inch Button Easy access Wire Inch button on front display enables user to feed wire without wasting shielding gas.



5 10004

Adjustable Burnback Control Adjusts stick-out and prevents wire from burning back.





Adjustable Soft & Hard start for optimum arc starting characteristics.

4.3" Blue LED Screen Bright screen allows for greater clarity in various welding conditions.

Thin Plate



0.6mm THIN SHEET car panel repairs.

BLUEVENOM XF190 P/N: W1400190

PACKAGE INCLUDES

- BLUEVENOM XF190 POWER SOURCE
- MIG GUN WITH EURO CONNECTION, 3m
- 300A WORK CLAMP, 3m LEAD
- TWISTLOCK ELECTRODE HOLDER, 3m LEAD
- FEED ROLLS: 0.8/0.9mm GASLESS - KNURLED, 0.8/0.9mm V GROOVE (FITTED)
- ARGON GAS HOSE, 2m
- GAS REGULATOR
- NYLON INLET GUIDE FOR SOFT WIRES
- OPERATING MANUAL







OPTIONAL ACCESSORIES & SPARES

BZL 15 Nozzle, 12mm, Pack of 2	BZN1512
BZL Contact Tip 0.6mm M6 L: 25mm, Pack of 10	BZT6606
BZL Contact Tip 0.8mm M6 L: 25mm, Pack of 10	BZT6608
BZL Contact Tip 0.9mm M6 L: 25mm, Pack of 10	BZT6609
BZL Contact Tip 1.0mm M6 L: 25mm, Pack of 10	BZT6610
BZL Contact Tip 1.2mm M6 L: 25mm, Pack of 10	BZT6612
BZL Contact Tip 1.4mm M6 L: 25mm, Pack of 10	BZT6614
BZL 15 Tip Holder, M6, LH, Pack of 2	BZH15L
MIG Front-end Kit Box BZL-15 LH	W4012303
Multi Liner Kit Steel 0.6-0.9mm, 5.1m	CML5K0609
Multi Liner Kit Steel 0.9-1.2mm, 5.1m	CML5K0912
Multi Liner Kit Aluminium 0.9-1.6mm, 4.5m	CML5K0916A
CIGWELD MIG Gun BZ15 Euro 3m (Marked as: CMGBZ15E3)	W52BR15E3
Nylon Inlet Guide (Soft Wires)	W7007384

TIG Torch 17V with 4m lead and gas valve	W4013801
TIG Torch 17V with 4m lead and gas valve a	and remote control W4013800
TIG Starter Kit 1 17/18/26 TIG Torches	CT1726K1
Tweco SGT250 Spool Gun	W4011250
TIG Foot Control with 7m Lead	W4015825
Argon Mini-Regulator and Gas Hose Kit incl Regulator/Flowmeter Side Inlet, Gas Hose 2	
WeldSkill Argon Regulator / Flowmeter, 55	5LPM, 2 Gauge 210254
CutSkill Preset Argon Regulator / Flowme	ter Side Inlet 201031
MIG Pliers, 8-Function	CWPLIER
WeldSkill Welding Equipment Trolley	W4011501
WeldSkill Welding Leadset 4m, 25mm ² cat DINSE, 250A Twistlock Electrode Holder	ble, 50mm² WS42550
WeldSkill Welding Leadset 5m, 35mm ² cat 400A Twistlock Electrode Holder	ble, 50mm² DINSE, WS53550

RELATED PRODUCTS

WeldSkill Heavy Duty Welding Gloves - Medium	646766
WeldSkill Heavy Duty Welding Gloves - Large	646755
WeldSkill Heavy Duty Welding Gloves – XL	646767
WeldSkill Welding Jacket - Medium	646771
WeldSkill Welding Jacket - Large	646772
WeldSkill Welding Jacket - XL	646773
WeldSkill Welding Jacket - XXL	646774
CIGWELD Heavy Duty Backpack	W4018001

Auto Darkening Welding Helmet Variable Shade 9-13 - Payday	WHAMXC130
Auto Darkening Welding Helmet Variable Shade 9-13 - Torque	WHAMXC120
WeldSkill Magnetic Welding Clamp/Holder - Medium	646764
WeldSkill Magnetic Welding Clamp/Holder - Large	646765
WeldSkill Welding Curtain – Dark Green, 1.74m x 1.74m	646770
WeldSkill Welding Curtain – Red, 1.74m x 1.74m	646777
Welding Curtain Frame, 1.8m x 1.8m	646776
Welding Blanket, 1.8m x 1.8m	646778

OPTIONAL FEED ROLLS

Feed Roll 0.6/0.8mm V Groove Solid Wires	FR302210V0608
Feed Roll 0.8/0.9mm V Groove Solid Wires (fitted on machine)	FR302210V0809
Feed Roll 1.0/1.2mm V Groove Solid Wires	FR302210V1012

Feed Roll 0.8/0.9mm U Groove Soft Wires	FR302210U0809
Feed Roll 1.0/1.2mm U Groove Soft Wires	FR302210U1012
Feed Roll 0.8/0.9mm V Knurled Flux Cored wires (included)	FR302210K0809

ORDERING DETAILS



BLUEVENOM XF190 PACKAGE P/N: W1400190

CIGWELD BlueVENOM XF190 V1-2023 CIGWELD Pty Ltd An ESAB Brand. www.cigweld.com.au





CIGWELD Pty Ltd An ESAB Brand 71 Gower Street, Preston VIC 3072 Australia CUSTOMER CARE: Tel: 1300 654 674 | Intl Tel: +61 9474 7400 Email: enquiries@cigweld.com.au

370128-01-623

CIGWELD.COM.AU
In the interest of continuous improvements, CIGWELD Pty Ltd ABN 56 007 226 815 (An ESAB Brand) reserves
the right to change specifications or design on any of its products without prior notice.