

SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : INDUSTRIAL SUPREME - ALL WEATHER PROTECTION LOW CONDUCTIVITY ANTIFREEZE/
COOLANT
Product code : 043810

1.2. Relevant identified uses of the substance or mixture and uses advised against

Application : Professional use. For industrial or institutional use. Antifreeze and de-icing products. Coolant.

1.3. Details of the supplier of the safety data sheet

Supplier : Star Brite
4041 SW 47th Avenue
33314 Fort Lauderdale, Florida
United States of America
Telephone : +1-954 587-6280
E-mail : info@starbrite.com
Website : http://www.starbrite.com

1.4 New Zealand Distributor

Distributor's name: WELDING ENGINEERS (NZ) LTD.
Address: 281 Church St, Onehunga, Auckland, New Zealand.

1.5 Emergency phone number

+64 9 6341949 between 8:00am-4.30pm; 0800 764 766 (0800 POISON) 24 hours.

SECTION 2 HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

GHS Classification (HCS : Acute toxicity, category 4. Specific target organ toxicity — repeated exposure, category 2. §1910.1200)

2.2. Label elements

Label elements (1910.1200)
Hazard pictograms :



Signal word : Warning

H- and P-phrases	:	H302	Harmful if swallowed.
		H373 kidneys	May cause damage to kidneys through prolonged or repeated exposure.
		P260 vapour	Do not breathe vapours.
		P264	Wash hands thoroughly after handling.
		P270	Do not eat, drink or smoke when using this product.
		P314	Get medical advice/attention if you feel unwell.
		P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
		P330	Rinse mouth.

P501

Dispose of contents/container to an official chemical waste depot.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

3.2. Mixtures

Product description : Mixture.

Information on hazardous substances:

Substance name	Concentration (w/w%)	CAS nr.	Additional CAS nr.	Hazards
Ethanediol	30 - < 60	107-21-1	-----	Acute Tox. 4; H302 STOT RE 2; H373
2,2' -Oxybisethanol	1 - < 5	111-46-6	-----	Acute Tox. 4; H302
1,2-Benzisothiazol-3(2H)-one	< 0,05	2634-33-5	-----	Acute Tox. 4; H302 Skin Irrit. 2; H315 Skin Sens. 1; H317 Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 2; H411

Occupational exposure limit(s), if relevant, are listed in section 8. The actual concentration has been withheld as a trade secret.

Reference is made to chapter 16 for full text of each relevant H phrase.

SECTION 4 FIRST-AID MEASURES

4.1. Description of first aid measures

First aid measures

- Inhalation : Move victim into fresh air. Consult a doctor if victim feels unwell.
- Skin contact : Take off contaminated clothing. Wash off skin with plenty of water and soap before product dries up. Consult a doctor if irritation occurs.
- Eye contact : Wash out with (lukewarm) water. Remove contact lenses. Consult a doctor if irritation persists.
- Ingestion : Do not induce vomiting. Do rinse the mouth. Give one glass of water. Never give anything by mouth to an unconscious person. Consult a doctor immediately if victim feels unwell.

4.2. Most important symptoms and effects, both acute and delayed

Effects and symptoms

- Inhalation : May cause headache, dizziness and a feeling of sickness.
- Skin contact : May produce an allergic reaction. May cause dry skin.
- Eye contact : May cause stinging of eyes and redness.
- Ingestion : May cause a feeling of sickness, vomiting and diarrhoea. May cause a feeling of sickness, malaise, shortness of breath and lack of breathe.

4.3. Indication of any immediate medical attention and special treatment needed

- Note to physicians :
- General : Risk of metabolic acidosis.

SECTION 5 FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

- Suitable : Carbondioxide (CO₂). Alcohol resistant foam. Dry chemical. Water fog.
Not suitable : Use of heavy stream of water may spread fire.

5.2. Special hazards arising from the substance or mixture

- Special exposure hazards : None known.
Hazardous thermal decomposition and combustion products : Carbon monoxide may be evolved if incomplete combustion occurs.

5.3. Advice for firefighters

- Special protective equipment for fire-fighters : Use adequate respiratory equipment in case of insufficient ventilation.
NFPA hazard rating :



SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

- Personal precautions : Danger of slipping. Clean up spills immediately. Wear shoes with non-slip soles. Avoid contact with spilled or released material. Vapours are heavier than air. Build up (of gasses) in low areas involves risk of suffocation.

6.2. Environmental precautions

- Environmental precautions : Avoid release of product into sewers, surface water and/or ground water. In case of large spills: contain with dike.
Other information : Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Collect spilled material in containers. Absorb residues in sand or other inert material. Dispose at an authorised waste collection point. Wash away remainder with plenty of water and soap.

6.4. Reference to other sections

- Reference to other sections : See also section 8.

SECTION 7 HANDLING AND STORAGE

7.1. Precautions for safe handling

- Handling : Handle in accordance with good occupational hygiene and safety practices in well-ventilated areas. Do not breathe vapour. Avoid contact with skin and eyes. Avoid splashing. Wear protective clothing.

7.2. Conditions for safe storage, including any incompatibilities

- Storage : Keep in a cool, dry and well-ventilated place. Keep away from oxidizing agents. Keep away from food, drink and animal feedingstuffs.
Recommended packaging : Keep only in the original container.

Non recommended packaging : Steel (except stainless steel).

7.3. Specific end use(s)

Use : Use only as directed.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits : Occupational exposure limits have not been established for this product.

Workplace exposure limits (mg/m³):

Chemical name	Country	TWA 8 hour (mg/m ³)	STEL 15 min (mg/m ³)	Comments	Source
Ethanediol	US	-	-	OEL Ceiling: 100 mg/m ³	ACGIH
2,2' -Oxybisethanol	US	10	-	-	OARS WEEL

8.2. Exposure controls

Engineering measures : Use only in well-ventilated areas. Comply with standard precautionary measures for working with chemicals.

Hygienic measures : When using do not eat, drink or smoke.

Personal protective equipment:

The efficiency of personal protective equipment depends among other things on temperature and degree of ventilation. Always get professional advice for the particular local situation.

Body protection : Use of specific protective industrial clothing is not required under normal conditions of use. In case of large scale exposure wear suitable protective clothing, overalls or suit, and similar boots. Suitable material: nitril. Indication of permeation breakthrough time: 6 hours.

Respiratory protection : Take care of sufficient ventilation. Wear suitable respiratory protection in case of large scale exposure. Suitable: gas filter type A (brown), class I or higher on e.g. a facemask.

Hand protection : Under normal conditions of use specific gloves are not required. Wear suitable gloves in case of frequent or prolonged use and in case of large scale exposure. Suitable material: nitril. ± 0,5 mm. Indication of permeation breakthrough time: 6 hours.

Eye protection : Wear appropriate safety glasses with side shields when there is danger of possible eye contact.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state : Liquid.
 Colour : Colourless.
 Odour : Characteristic.
 Odour threshold : Not known.
 pH : 8
 Solubility in water : Soluble.
 Partition coefficient (n-octanol/water) : Not known. Not measured. Not relevant for mixtures.
 Flash point : > 100 °C Closed Cup (ISO 2719, EN 11, DIN 51758, ASTM D 93).
 Flammability (solid, gas) : Not applicable. Liquid. See flashpoint.
 Auto ignition temperature : > 180 °C
 Boiling point/boiling range : > 100 °C

Freezing point	: -40 °C	
Explosion limits (% in air)	: Not known.	Lower explosion limit in air (%): 0.7 (2,2' -Oxybisethanol)
	:	Upper explosion limit in air (%): 37 (2,2' -Oxybisethanol)
Oxidising properties	: Not applicable.	Does not contain oxidizing substances.
Decomposition temperature	: Not applicable.	
Viscosity (20°C)	: Not known.	
Viscosity (40°C)	: Not relevant.	The product contains < 10% substances having an aspiration hazard.
Vapour pressure (20°C)	: Not known.	
Relative vapour density	: > 1	(air = 1)
Relative density (20°C)	: 1,08 g/ml	
Evaporation rate	: Not known.	(n-butyl acetate = 1)

SECTION 10 STABILITY AND REACTIVITY
--

10.1. Reactivity

Reactivity : See sub-sections below.

10.2. Chemical stability

Stability : Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactivity : No other hazardous reactions known.

10.4. Conditions to avoid

Conditions to avoid : See section 7.

10.5. Incompatible materials

Materials to avoid : Keep away from oxidizing agents.

10.6. Hazardous decomposition products

Hazardous decomposition products : Not known.

SECTION 11 TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

No toxicological research has been carried out on this product.

Inhalation

Acute toxicity	: Calculated LC50: > 2,628 mg/l. Ingredients of unknown toxicity: < 1 %. ATE: > 5 mg/l. Low toxicity. Not classified - based on available data, the classification criteria are not met. May cause headache, dizziness and a feeling of sickness.
Corrosion/irritation	: Not classified - based on available data, the classification criteria are not met.
Sensitisation	: Does not contain substances classified as respiratory sensitiser. Not classified - based on available data, the classification criteria are not met.
Carcinogenicity	: Not classified - based on available data, the classification criteria are not met.
Mutagenicity	: Not expected to be mutagenic. Not classified - based on available data, the classification criteria are not met.

Skin contact

- Acute toxicity : Calculated LD50: > 5000 mg/kg.bw. Ingredients of unknown toxicity: < 1 %. ATE: > 5000 mg/kg.bw. Low toxicity. Not classified - based on available data, the classification criteria are not met.
- Corrosion/irritation : Slight irritation possible. Not classified - based on available data, the classification criteria are not met.
- Sensitisation : May produce an allergic reaction.
- Mutagenicity : Does not contain mutagenic substances. Not classified - based on available data, the classification criteria are not met.
- Eye contact
- Corrosion/irritation : Slight irritation possible. Not classified - based on available data, the classification criteria are not met.
- Ingestion
- Acute toxicity : May cause signs of intoxication and reduced consciousness after exposure to high concentrations. May cause a feeling of sickness, malaise, shortness of breath and lack of breathe. Calculated LD50: > 5000 mg/kg.bw. Ingredients of unknown toxicity: < 1 %. ATE: 500 mg/kg.bw.
- Aspiration : Not classified - based on available data, the classification criteria are not met. Does not contain substances with an aspiration hazard.
- Chronic toxicity : Possibility of organ or organ system damage due to prolonged exposure. Target organ(s): Kidneys. Effect: May cause nephrolithiasis.
- Corrosion/irritation : May cause a feeling of sickness, vomiting and diarrhoea.
- Carcinogenicity : Not classified - based on available data, the classification criteria are not met.
- Mutagenicity : Not expected to be mutagenic. Not classified - based on available data, the classification criteria are not met.

Toxicological information:

Chemical name	Property		Method	Test animal
Ethanediol	NOAEL (development, oral)	250 mg/kg bw/d		Rat
	LD50 (dermal)	10600 mg/kg bw		
	Mutagenicity	Not mutagenic		
	Genotoxicity - in vitro	Not genotoxic		
	Skin irritation	Non-irritant		Rabbit
	Skin sensitisation	Not sensitizing	OECD 406	Guinea pig
	NOEL (inhalation)	71 mg/m3		
	LD50 (oral)	7712 mg/kg bw	----	Rat
	Eye irritation	Non-irritant		Rabbit
	LD50 (oral) - estimate	500 mg/kg bw		
	LC50 (inhalation)	> 2500 mg/m3	----	Rat
	LC50 (inhalation) - estimate	> 5000 mg/m3		
	NOAEL (oral)	150 mg/kg bw/d	OECD 452	Rat
	NOEL (carcinogenicity, oral)	1000 mg/kg bw/d		Rat
2,2' -Oxybisethanol	Mutagenicity	Negative	OECD 471	Salmonella typhimurium
	Genotoxicity - in vivo	> 2000 mg/kg bw/d	OECD 474	Mouse
	LD50 (oral) - estimate	1000 mg/kg bw	----	Human
	LC50 (inhalation)	130 mg/m3	----	Mouse
	LD50 (oral)	19600 mg/kg bw	----	Rat
	NOAEL (oral)	50 mg/kg bw/d		Rat
	Skin irritation	Non-irritant		
	Eye irritation	Non-irritant		
	Genotoxicity - in vitro	Not genotoxic		
	NOAEL (fertility, oral)	612 mg/kg bw/d		Mouse
	NOAEL (development, oral)	1250 mg/kg bw/d		Mouse
	Skin sensitisation	Not sensitizing	OECD 406	Guinea pig

1,2-Benzisothiazol-3(2H)-one	NOAEL (dermal) - estimate	3549 mg/kg bw/d	----	Mouse
	Genotoxicity - estimate	Not genotoxic		Mouse
	NOEL (carcinogenicity, oral)	1160 mg/kg bw/d		Rat
	LD50 (dermal) - estimate	> 5000 mg/kg bw	----	Rabbit
	LC50 (inhalation) - estimate	> 5000 mg/m3		Rat
	LD50 (oral)	670 mg/kg bw	OECD 401	Rat
	Skin irritation	Irritant		Rabbit
	Eye irritation	Severely irritant		Rabbit
	Skin sensitisation	Sensitizing.	OECD 406	Guinea pig
	NOAEL (oral)	30 mg/kg bw/d	OECD 408	Rat
	Genotoxicity - in vitro	Genotoxic	OECD 473	
	Genotoxicity - in vivo	250 mg/kg bw/d	OECD 474	Mouse
	NOAEL (development, oral)	Not teratogenic		
	NOAEL (fertility, oral)	24 mg/kg bw/d		Rat
LD50 (dermal)	> 4115 mg/kg bw	OECD 402	Rat	

Other information : Ethanediol: There is a marked difference in acute oral toxicity between rodents and man, man being more susceptible than rodents. The estimated fatal dose for man is 100 millilitres (1/2 cup).

11.2. Information on other hazards

Other information : No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens. No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12 ECOLOGICAL INFORMATION

12.1. Toxicity

No ecotoxicological research has been carried out on this product.

Ecotoxicity : Calculated LC50 (fish): 1280 mg/l. Calculated EC50 (waterflea): 170 mg/l. Contains 0 % of components with unknown hazards to the aquatic environment.

12.2. Persistence and degradability

Persistence – degradability : No specific information known.

12.3. Bioaccumulative potential

Bioaccumulative potential : No specific information known.

12.4. Mobility in soil

Mobility : If product enters soil, it will be highly mobile and may contaminate groundwater.

12.7. Other adverse effects

Other adverse effects : Not applicable.

SECTION 13 DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

- Product residues : Do not dispose empty pack with waste produced by households. Containers may be recycled. Treat product residues and non-empty pack as hazardous waste.
- Additional warning : None.
- Waste water discharge : Do not dispose of into the environment, drains, sewers or water courses.
- Local legislation : Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.

SECTION 14 TRANSPORT INFORMATION

14.1. UN number or ID number

UN nr. : None.

14.2. UN proper shipping name

Transport name : Not regulated.

14.3/14.4/14.5. Transport hazard class(es)/Packing group/Environmental hazards

DOT (land)

Class : This product is not classified according to DOT.

IMDG (sea)

Class : This product is not classified according to IMDG.

Marine pollutant : No

IATA (air)

Class : This product is not classified according to IATA.

14.6. Special precautions for user

Other information : Country specific variations may apply.

14.7. Maritime transport in bulk according to IMO instruments

Marpol : Not intended to be carried in bulk according to International Maritime Organisation (IMO) instruments. Packaged liquids are not considered bulk.

SECTION 15 REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations : OSHA HazCom 2012, 29 CFR 1910.1200 and other Regulations.

United States TSCA (Toxic Substances Control Act) inventory

: All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

US State Regulation

California Proposition 65



SAFETY DATA SHEET

According to OSHA HazCom 2012, 29 CFR 1910.1200

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm

Chemical name	CAS	Type of toxicity	NSRL or MADL (ug/d)
Ethenediol	107-21-1	developmental	8700 (oral)
1,4-Dioxane	123-91-1	cancer	30
Acetaldehyde	75-07-0	cancer	90 (inhalation)
2-Methoxyethanol	109-86-4	developmental	63 (oral)
2-Methoxyethanol	109-86-4	male	63 (oral)

SECTION 16 OTHER INFORMATION

16.1. Other information

The information in this safety data sheet is compiled in compliance with Hazcom 1910.1200. It is the user's obligation to use this product safely and to comply with all applicable laws and regulations concerning the use of the product. This safety data sheet complements the technical information sheets but does not replace them and offers no warranty with regard to product properties.

Users are also forewarned for any hazards involved when the product is used for other purposes than those for which it is designed.

Changed or new information with regard to the previous release is indicated with an asterisk (*).

List of abbreviations and acronyms that could be (but not necessarily are) used in this safety data sheet:

ATE	: Acute Toxicity Estimate
CMR	: Carcinogenic, Mutagenic or toxic for Reproduction
DOT	: Department of Transportation
DSL	: Domestic Substances List
GHS	: Globally Harmonized System of Classification and Labelling of Chemicals
HPA	: Hazardous Products Act
HPR	: Hazardous Products Regulations
IATA	: International Air Transport Association
IBC code	: International Bulk Chemical Code
IMDG	: International Maritime Dangerous Goods Code
LD50/LC50	: Lethal Dose/Concentration for 50% of a population
MARPOL	: International Convention for the Prevention of Pollution From Ships
NO(A)EL	: No Observed (Adverse) Effect Level
OECD	: Organisation for Economic Co-operation and Development
OSHA	: United States Occupational Safety and Health Administration
PBT	: Persistent, Bioaccumulative and Toxic
REACH	: Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	: Regulations concerning the International Carriage of Dangerous Goods by Rail
STP	: Sewage Treatment Plant
TWA/STEL	: Time-Weighted Average/Short Term Exposure Limit
UN	: United Nations
VOC	: Volatile Organic Compounds
vPvB	: Very Persistent and Very Bioaccumulative
WHMIS	: Workplace Hazardous Materials Information System

Key data used to compile the Safety Data Sheet are from, but not limited to, one or more sources of information e.g. toxicological data from material suppliers, CONCAWE, IFRA, CESIO, Regulation EG 1272/2008, etc. Also used: OSHA HazCom 2012, 29 CFR 1910.1200.

Full text of H-phrases mentioned in section 3:

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H373	May cause damage to organs through prolonged or repeated exposure.

Product name : Industrial Supreme - All Weather Protection Low Conductivity Antifreeze/
Coolant

Page 9/10

Date of issue : 2023-02-09 Replaces issue dated : ---

INFO CARE SDS



SAFETY DATA SHEET

According to OSHA HazCom 2012, 29 CFR 1910.1200

H400 Very toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.

Advice on any training appropriate for workers: none.

Number format : "," used as decimal separator.

Date of preparation or latest revision : 2023-02-09

End of safety data sheet.